

## CO ALARM

### Product Code: LM-201A

Type:	Carbon Monoxide Detector
Detection Method:	Electronic & Chemical Sensor
Dimensions:	90mm x 120mm x 40mm
Power:	3 x 1.5V AA alkaline batteries
Operating Temperature:	0°C - 45°C
Environmental Humidity:	0% - 90%
Standby Consumption:	80uA
Consumption during use:	45-75mA
Alarm:	>85dB (1 meter)
Display Scope:	25-550 PPM ( $\pm 10\%$ )
Battery Indicator	
Pause Function	
CO Level Indicator	



Parts Per Million (PPM) of CO	Time Until Alarm Activates
50 PPM	60 - 90 Minutes
100 PPM	10 - 40 Minutes
300 PPM	Less than 3 Minutes

### Features:

This alarm is designed to protect you and your family from carbon monoxide poisoning.  
 Test button and Led indicator light  
 With LCD Display  
 Low Battery Warning  
 Easy to install  
 Up to 7 years working life span from first power up  
 LCD display shows the carbon monoxide particle sampling count, ambient temperature and battery level.  
 LED status indicators, green for power , yellow for fault and red for alarm  
 Battery powered to allow the unit to remain functional in the event of a power cut.  
 Manufactured to EN50291  
 Comply to ROHS Standards

Note: This apparatus must be installed according to the manufactures instruction.