

Copper Lug Terminal

Product Description:

Copper Lug Terminal



Specifications:

Bell mouth for easier cable insertion
Electro-tin plated to BS1872, 1984
Pure grade copper base to BS2871
RoHS Compliant

Characteristics:

- AWG wire size and stud size identification on the lug
- Enable universal use with one studs/screws to fix on equipments
- Design the fixes close-end structure with stub to ensure connection reliability
- Full anneal(HV60) to ensure the compression effect
- Inspection sight hole to inspect right of cable insertion

Code	Stub(Metric)	mm ²	A.W.G	Pack Qty
ACL1.5-3	3	1.5		100
ACL1.5-4	4	1.5		100
ACL1.5-5	5	1.5		100
ACL2.5-3	3	2.5		100
ACL2.5-4	4	2.5		100
ACL2.5-5	5	2.5		100
ACL2.5-6	6	2.5		100
ACL4-6	6	4		50
ACL6-10	10	4-6	12-10	50
ACL6-4	4	4-6	12-10	50
ACL6-5	5	4-6	12-10	50
ACL6-6	6	4-6	12-10	50
ACL6-8	8	4-6	12-10	50
ACL10-10	10	10	8	50
ACL10-12	12	10	8	50
ACL10-5	5	10	8	50
ACL10-6	6	10	8	50
ACL10-8	8	10	8	50
ACL10BLNK	Blank	10	8	50
ACL16-10	10	16	6	25

ACL16-12	12	16	6	25
ACL16-5	5	16	6	25
ACL16-6	6	16	6	25
ACL16-8	8	16	6	25
ACL16BLNK	Blank	16	6	25
ACL25-10	10	25	4	25
ACL25-12	12	25	4	25
ACL25-6	6	25	4	25
ACL25-8	8	25	4	25
ACL25BLNK	Blank	25	4	25
ACL35-10	10	35	2	20
ACL35-12	12	35	2	20
ACL35-14	14	35	2	20
ACL35-6	6	35	2	20
ACL35-8	8	35	2	20
ACL35BLNK	Blank	35	2	20
ACL50-10	10	50	1/0	10
ACL50-12	12	50	1/0	10
ACL50-14	14	50	1/0	10
ACL50-16	16	50	1/0	10
ACL50-6	6	50	1/0	10
ACL50-8	8	50	1/0	10
ACL50BLNK	Blank	50	1/0	10
ACL70-10	10	70	2/0	10
ACL70-12	12	70	2/0	10
ACL70-14	14	70	2/0	10
ACL70-16	16	70	2/0	10
ACL70-6	6	70	2/0	10
ACL70-8	8	70	2/0	10
ACL70BLNK	Blank	70	2/0	10
ACL95-10	10	95	3/0	5
ACL95-12	12	95	3/0	5
ACL95-14	14	95	3/0	5
ACL95-16	16	95	3/0	5
ACL95-20	20	95	3/0	5
ACL95-8	8	95	3/0	5
ACL95BLNK	Blank	95	3/0	5
ACL120-10	10	120	4/0	5
ACL120-12	12	120	4/0	5
ACL120-14	14	120	4/0	5
ACL120-16	16	120	4/0	5
ACL120-8	8	120	4/0	5
ACL120BLNK	Blank	120	4/0	5
ACL150-10	10	150	250/300	4
ACL150-12	12	150	250/300	4
ACL150-14	14	150	250/300	4
ACL150-16	16	150	250/300	4

ACL150-20	20	150	250/300	4
ACL150-8	8	150	250/300	4
ACL150BLNK	Blank	150	250/300	4
ACL185-10	10	185	300/350	4
ACL185-12	12	185	300/350	4
ACL185-14	14	185	300/350	4
ACL185-16	16	185	300/350	4
ACL185-20	20	185	300/350	4
ACL185BLANK	Blank	185	300/350	4
ACL240-10	10	240	400/450	4
ACL240-12	12	240	400/450	4
ACL240-14	14	240	400/450	4
ACL240-16	16	240	400/450	4
ACL240-20	20	240	400/450	4
ACL240BLNK	Blank	240	400/450	4
ACL300-10	10	300	500/600	4
ACL300-12	12	300	500/600	4
ACL300-14	14	300	500/600	4
ACL300-16	16	300	500/600	4
ACL300-20	20	300	500/600	4
ACL300BLANK	Blank	300	500/600	4
ACL400-12	12	400	600/750	4
ACL400-14	14	400	600/750	4
ACL400-16	16	400	600/750	4
ACL400-20	20	400	600/750	4
ACL400BLANK	Blank	400	600/750	4
ACL500-16	16	500	800/1000	2
ACL500-20	20	500	800/1000	2
ACL500BLNK	Blank	500	800/1000	2