

MICROPHONE CABLE MIC0022BLK

Product Description:

CABLE MICROPHONE 3MM BLACK 100M



Superb quality, highly flexible microphone cable suitable for use in studio, stage and general A/V applications.



Construction:

Conductor:	20/0.10 mm (BC OFC)
Insulation:	PE
Insulation Color:	Red, White
Insulation Dia./Thickness:	1.1±0.10 mm / 0.29±0.08 mm
Drain Wire:	7/0.20 mm (TC OFC)
Wrap:	AL-Foil
Shielding	AL
Shielding Coverage	100%
Jacket:	PVC
Jacket Color:	Black
Jacket Dia./Thickness:	3.0±0.10 mm / 0.36mm

Electrical Characteristics:

Rated Temperature: 60°C

Conductor Resistance (at 20 $^{\circ}$ C): 121.01 Ω /km

Packaging:

100M/Paper Spool

Other Standard:

RoHS Compliant

Datasheet Ref: Microphone Cable

Issue: 1

Page 1 of 1

This data sheet remains the property and copyright of C & C Cables Limited and the information contained within this document must not be copied or reproduced without the permission, in writing, from C & C Cables Limited. All information contained within this data sheet was correct at time of creation but may be subject to change without prior notice.

C & C Cables Limited Unit OA, Time Technology Park, Blackburn Road, Simonstone, Burnley, Lancs, BB12 7NQ, UK