

Commtech Trading Ltd

Unit OA, Time Technology Park, Blackburn Road, Simonstone, Burnley, Lancs, BB12 7TY, UK
Tel: 01254 777 987 Fax: 01282 787 790 E-mail: sales@shinnthon.com

Code: PE10130

C19 16A Chassis Socket

Features:

- Panel Mount: Screw-on mounting from front side
- 1 Function
- Connector, Pin temperature 70 °C, Protection class I
- Solder terminals or quick connect terminals



Technical Data:

Ratings IEC :16 A / 250 VAC; 50 Hz

Ratings UL/CSA 20 A / 250 VAC; 60 Hz

Dielectric Strength > 2 kVAC between L-N > 2 kVAC between L/N-PE (1 min/50 Hz)

Allowable Operation Temp. -25 °C to 70 °C

Degree of Protection from front side IP 30 acc. to IEC 60529

Protection Class Suitable for appliances with protection class I acc. to IEC 61140 Terminal

Solder terminals or quick connect terminals

Panel Thickness s Screw: max 8 mm Mounting screw torque max 0.5 Nm

Material: Housing Thermoplastic, black, UL 94V-0

Approvals:



Complies to:



Issue Date:02/06/2020
Revision: 1

Dimensions and images may differ from those shown