

Shinn Thon UK Ltd

1st Floor, 223 Dalton Road, Barrow in Furness, Cumbria. LA14 1PQ
Tel: 0870 609 2264 Fax: 01229 833 733 E-mail: sales@shinnthon.com

Product Datasheet

SH5008

Paper Masking Tape 50M



Specifications:

Nature color crepe paper wit adhesive

Coated with synethctic Rubber

Nature color crepe pape

Width: 19mm/25mm/38mm/50mm

Applications

Sealing applications

Hole closure masking

Interior use

Packaging, holding and bundling

Technology Data:

Total thickness	Adhesive to steel	Tensile Strength	Rolling ball tack	Elongation	Holding power	Service temperature range
(mm)	(oz/inch)	(N/CM)	(Ball no.)	(N/CM)	(Hours)	(°C)
0.12	18.28	>20	5	N/A	N/A	-0°C -> +60°C

Dimensions may differ from those shown

Shinn Thon UK Ltd

1st Floor, 223 Dalton Road, Barrow in Furness, Cumbria. LA14 1PQ
Tel: 0870 609 2264 Fax: 01229 833 733 E-mail: sales@shinnthon.com

Usage:

Temperature: between 0°C and + 35°C. Surface must be clean and free from dust and grease. Avoid touching the tapes exposed adhesive surface in order to keep full adhesive performance. Pressure sensitive adhesive must be applied with a maximum of pressure in order to achieve maximum pressure level. The indicated level of performance will be reached after a bonding period of 24 HRS at 23 °C.

Storage and shelf life

Clean and dry in a well ventilated area, preferably at a temperature between 10°C and 30°C. Stored under these conditions shelf life will be a minimum of 6 months.

Complies to:

RoHS 2011/65/EU

Issue Date: 01/01/2013
Revision: E