

## SHWOLVO

**Polyolefin material; Skidproof Heat Shrink Tubing.**

### Characteristics

- Minimum shrink temperature: 70°C
- Minimum fully recovery temperature: 110°C
- Operating temperature: -55°C ~ 105°C
- Good flexibility, abrasion resistant and anti-skid performance
- RoHS Compliant
- Standard color: black, red, yellow, white, green, blue



### Applications

It is Widely used in various fishing tackles, sport fittings, equipments and commodities with hand device.

### Technical Data

Property	Test Method	Typical Data
Tensile Strength (MPa)	ASTM D 412	10.4
Longitudinal Elongation (%)	ASTM D 412	≤8
Elongation (%)	ISO 1210	200

### Product Dimensions

Size	As supplied(mm)		After recovery(mm)		Standard Package
	Internal Diameter (mm)	Average Thickness	MAX Internal Diameter (mm)	Average Thickness	M/PC
15	≥15	0.45±0.15	8	0.85±0.15	1.0
20	≥20	0.50±0.15	11	0.90±0.15	0.8/1.0/1.6
22	≥22	0.50±0.15	12.5	0.90±0.15	0.8/1.0/1.6
25	≥25	0.50±0.15	14.5	1.00±0.15	0.8/1.0/1.6
28	≥28	0.50±0.15	15.5	1.00±0.15	0.8/1.0/1.6

30	$\geq 30$	$0.60 \pm 0.15$	17.5	$1.20 \pm 0.15$	0.8/1.0/1.6
35	$\geq 35$	$0.60 \pm 0.15$	20	$1.20 \pm 0.15$	0.8/1.0/1.6
40	$\geq 40$	$0.60 \pm 0.15$	23	$1.20 \pm 0.15$	0.8/1.0/1.6
45	$\geq 45$	$0.65 \pm 0.15$	25	$1.25 \pm 0.15$	0.8/1.0/1.6
50	$\geq 50$	$0.65 \pm 0.15$	28	$1.25 \pm 0.15$	0.8/1.0/1.6